

Data sheet

Item no. / Configuration 01 / 2102132-7.50-040201-S-A00430
Description HMA2 132S2-2 400/690 V 50 Hz 7,5 kW

General data	
Standard series	IEC 60034
Type	HMA2 132S2-2
Design	400 VD / 690 VY 50 Hz + 480 VD / 830 VY 60 Hz
Direction of rotation	CW
Installation max. altitude (m)	1.000
Poles	2

Motor protection	
Winding temp. detector	No
Temp. detector type	None
Bearing detector	No
Winding PTC main	PTC 3 x 155°C
Winding PTC spare	None
Space heater	None
Terminal board thread	M5
Electrical insulation	Standard (1350 V @ 0.8 µs)
Tropical insulation	Yes
SPM	N/A
External grounding	Yes
Drain hole	Yes
Rain cap	No

Classification	
Class society	
Shaft requirement acc. to	None
Ex. code	No

Mechanical data	
Frame / Shaft height	IEC 132
Type of construction	B35
Cooling method	IC411
Protection class	IP55
Temp. insulation class	F
Frame material	Aluminum
Keyway	Closed
Balancing	Half key
IEC vibration class	A
Weight (kg)	51
Bearing (DE)	6308 2Z / C3 / DGBB
Bearing (NDE)	6308 2Z / C3 / DGBB
Fixed bearing	DE
Moment of inertia (kg×m ²)	0.016
Painting (color)	RAL 9005
Corrosion protection	C3L
Main terminal box pos.	DE top
Main cable entries	Cable gland 2xM25x1.5 Ø11-17 mm
Main cable direction	Right from DE
Main cable material	Nickel plated brass
Aux. cable entries	Blind cap 1xM20x1.5
Aux. cable direction	NDE
Aux. cable material	Nickel plated brass

Winding operation variants						
Rated power (kW)	7.5	7.28	8.73			
Frequency (Hz)	50	50	60			
Connection	D/Y	D/Y	D/Y			
Voltage (V)	400 / 690	380 / 660	440 /			
Full load current (A)	13.5 / 7.78	14.7 / 8.5	14.3 /			
No load current (A)	3.75	4.37	4.87			
Speed (rpm)	2919	2919	3503			
Power factor 100/75/50 (%)	0.91 / 0.89 / 0.82	0.92 / 0.9 / 0.83	0.91 / 0.89 / 0.82			
Efficiency 100/75/50 (%)	88.1 / 88.7 / 87.9	88.1 / 88.7 / 87.9	88.1 / 88.7 / 87.9			
Efficiency class	IE2	IE2	IE1			
Full load torque (Nm)	24.5	23.8	23.8			
Tst/Tn	2.2	2.02	2.19			
Tmax/Tn	3	2.75	3			
Ist/In	8.01	7.1	8.25			
Temp. rise class	B	B	B			
Duty	S1	S1	S1			
Sound pressure level (dBA)	74	74	79			
Min. ambient temp. (°C)	-20°C	-20°C	-20°C			
Max. ambient temp. (°C)	40°C	45°C	45°C			

Data are not binding. Hoyer reserves the right to implement changes without notice. The extent of data are not equivalent to nameplate on the motors.