

# HOYER

MOTORS

## Data sheet

**Item no. / Configuration** 01 / 3104100-3.00-030101-S-A00746  
**Description** HMA3 100L2-4 B14 3kW IE3@50 230/400@50 RAL9005

General data	
Standard series	IEC 60034
Type	HMA3 100L2-4
Design	230 VD / 400 VY 50 Hz + 280 VD / 480 VY 60 Hz
Direction of rotation	CW
Installation max. altitude (m)	1.000
Poles	4

Motor protection	
Winding temp. detector	No
Temp. detector type	None
Bearing detector	No
Winding PTC main	PTC 3 x 155°C
Winding PTC spare	None
Space heater	None
Terminal board thread	M4
Electrical insulation	Standard (1350 V @ 0.8 µs)
Tropical insulation	No
SPM	N/A
External grounding	No
Drain hole	Yes
Rain cap	No

Classification	
Class society	
Shaft requirement acc. to	None
Ex. code	No

Mechanical data	
Frame / Shaft height	IEC 100
Type of construction	B14
Cooling method	IC411
Protection class	IP55
Temp. insulation class	F
Frame material	Aluminum
Keyway	Closed
Balancing	Half key
IEC vibration class	A
Weight (kg)	33
Bearing (DE)	6206 2Z / C3 / DGBB
Bearing (NDE)	6206 2Z / C3 / DGBB
Fixed bearing	DE
Moment of inertia (kg×m <sup>2</sup> )	0.012
Painting (color)	RAL 9005
Corrosion protection	C3L
Main terminal box pos.	DE top
Main cable entries	Blind cap 2xM20x1.5
Main cable direction	Right from DE
Main cable material	Plastic
Aux. cable entries	Blind cap 1xM20x1.5
Aux. cable direction	NDE
Aux. cable material	Plastic

Winding operation variants	
Rated power (kW)	3
Frequency (Hz)	50
Connection	D/Y
Voltage (V)	230 / 400
Full load current (A)	10.7 / 6.16
No load current (A)	3.33
Speed (rpm)	1458
Power factor 100/75/50 (%)	0.8 / 0.73 / 0.6
Efficiency 100/75/50 (%)	87.7 / 87.9 / 86.4
Efficiency class	IE3
Full load torque (Nm)	19.7
Tst/Tn	3.5
Tmax/Tn	3.8
Ist/In	9.03
Temp. rise class	B
Duty	S1
Sound pressure level (dBA)	56
Min. ambient temp. (°C)	-20°C
Max. ambient temp. (°C)	40°C

Data are not binding. Hoyer reserves the right to implement changes without notice. The extent of data are not equivalent to nameplate on the motors.