

HOYER

MOTORS

Data sheet

Item no. / Configuration 01 / 3104100-3.00-040101-S-A00749
Description HMA3 100L2-4 B35 3kW IE3@50 230/400@50 RAL9005

| General data | |
|--------------------------------|---|
| Standard series | IEC 60034 |
| Type | HMA3 100L2-4 |
| Design | 230 VD / 400 VY 50 Hz + 280 VD / 480 VY 60 Hz |
| Direction of rotation | CW |
| Installation max. altitude (m) | 1.000 |
| Poles | 4 |

| Motor protection | |
|------------------------|----------------------------|
| Winding temp. detector | No |
| Temp. detector type | None |
| Bearing detector | No |
| Winding PTC main | PTC 3 x 155°C |
| Winding PTC spare | None |
| Space heater | None |
| Terminal board thread | M4 |
| Electrical insulation | Standard (1350 V @ 0.8 µs) |
| Tropical insulation | No |
| SPM | N/A |
| External grounding | No |
| Drain hole | Yes |
| Rain cap | No |

| Classification | |
|---------------------------|------|
| Class society | |
| Shaft requirement acc. to | None |
| Ex. code | No |

| Mechanical data | |
|--|---------------------|
| Frame / Shaft height | IEC 100 |
| Type of construction | B35 |
| Cooling method | IC411 |
| Protection class | IP55 |
| Temp. insulation class | F |
| Frame material | Aluminum |
| Keyway | Closed |
| Balancing | Half key |
| IEC vibration class | A |
| Weight (kg) | 33 |
| Bearing (DE) | 6206 2Z / C3 / DGBB |
| Bearing (NDE) | 6206 2Z / C3 / DGBB |
| Fixed bearing | DE |
| Moment of inertia (kg×m ²) | 0.012 |
| Painting (color) | RAL 9005 |
| Corrosion protection | C3L |
| Main terminal box pos. | DE top |
| Main cable entries | Blind cap 2xM20x1.5 |
| Main cable direction | Right from DE |
| Main cable material | Plastic |
| Aux. cable entries | Blind cap 1xM20x1.5 |
| Aux. cable direction | NDE |
| Aux. cable material | Plastic |

| Winding operation variants | |
|----------------------------|--------------------|
| Rated power (kW) | 3 |
| Frequency (Hz) | 50 |
| Connection | D/Y |
| Voltage (V) | 230 / 400 |
| Full load current (A) | 10.7 / 6.16 |
| No load current (A) | 3.33 |
| Speed (rpm) | 1458 |
| Power factor 100/75/50 (%) | 0.8 / 0.73 / 0.6 |
| Efficiency 100/75/50 (%) | 87.7 / 87.9 / 86.4 |
| Efficiency class | IE3 |
| Full load torque (Nm) | 19.7 |
| Tst/Tn | 3.5 |
| Tmax/Tn | 3.8 |
| Ist/In | 9.03 |
| Temp. rise class | B |
| Duty | S1 |
| Sound pressure level (dBA) | 56 |
| Min. ambient temp. (°C) | -20°C |
| Max. ambient temp. (°C) | 40°C |

Data are not binding. Hoyer reserves the right to implement changes without notice. The extent of data are not equivalent to nameplate on the motors.