

## Data sheet

**Item no. / Configuration** 01 / 4102132-5.50-030201-S-026782  
**Description** HMA4 132S1-2 400/690 V 50 Hz 5,5 kW

| General data                   |   |
|--------------------------------|---|
| Standard series                | IEC 60034                                     |
| Type                           | HMA4 132S1-2                                  |
| Design                         | 400 VD / 690 VY 50 Hz + 480 VD / 830 VY 60 Hz |
| Direction of rotation          | CW  |
| Installation max. altitude (m) | 1.000   |
| Poles                          | 2   |

| Motor protection       |                            |
|------------------------|----------------------------|
| Winding temp. detector | No                         |
| Temp. detector type    | None                       |
| Bearing detector       | No                         |
| Winding PTC main       | PTC 3 x 155°C              |
| Winding PTC spare      | None                       |
| Space heater           | None                       |
| Terminal board thread  | M5                         |
| Electrical insulation  | Standard (1350 V @ 0.8 µs) |
| Tropical insulation    | No                         |
| SPM                    | N/A                        |
| External grounding     | No                         |
| Drain hole             | Yes                        |
| Rain cap               | No                         |

| Classification            |      |
|---------------------------|------|
| Class society             |      |
| Shaft requirement acc. to | None |
| Ex. code                  | No   |

| Mechanical data                        |                     |
|--|---------------------|
| Frame / Shaft height                   | IEC 132             |
| Type of construction                   | B14                 |
| Cooling method                         | IC411               |
| Protection class                       | IP55                |
| Temp. insulation class                 | F                   |
| Frame material                         | Aluminum            |
| Keyway                                 | Closed              |
| Balancing                              | Half key            |
| IEC vibration class                    | A                   |
| Weight (kg)                            | 54                  |
| Bearing (DE)                           | 6308 2Z / C3 / DGBB |
| Bearing (NDE)                          | 6308 2Z / C3 / DGBB |
| Fixed bearing                          | DE                  |
| Moment of inertia (kg×m <sup>2</sup> ) | 0.0167              |
| Painting (color)                       | RAL 9005            |
| Corrosion protection                   | C3L                 |
| Main terminal box pos.                 | DE top              |
| Main cable entries                     | Blind cap 2xM25x1.5 |
| Main cable direction                   | Right from DE       |
| Main cable material                    | Plastic             |
| Aux. cable entries                     | Blind cap 1xM20x1.5 |
| Aux. cable direction                   | NDE                 |
| Aux. cable material                    | Plastic             |

| Winding operation variants |                      |                      |  |
|----------------------------|----------------------|----------------------|--|
| Rated power (kW)           | 5.5                  | 5.5                  |  |
| Frequency (Hz)             | 50                   | 60                   |  |
| Connection                 | D/Y                  | D/Y                  |  |
| Voltage (V)                | 400 / 690            | 480 / 830            |  |
| Full load current (A)      | 9.92 / 5.75          | 8.33 / 4.82          |  |
| No load current (A)        | 3.65                 | 3.76                 |  |
| Speed (rpm)                | 2930                 | 3530                 |  |
| Power factor 100/75/50 (%) | 0.88 / 0.83 / 0.73   | 0.88 / 0.74 / 0.63   |  |
| Efficiency 100/75/50 (%)   | 90.9 / 91.99 / 91.43 | 90.2 / 92.82 / 91.98 |  |
| Efficiency class           | IE4                  | IE4                  |  |
| Full load torque (Nm)      | 17.9                 | 14.7                 |  |
| Tst/Tn                     | 2.79                 | 3.65                 |  |
| Tmax/Tn                    | 3.89                 | 4.82                 |  |
| Ist/In                     | 9.06                 | 13                   |  |
| Temp. rise class           | B                    | B                    |  |
| Duty                       | S1                   | S1                   |  |
| Sound pressure level (dBA) | 63                   | 69                   |  |
| Min. ambient temp. (°C)    | -20°C                | -20°C                |  |
| Max. ambient temp. (°C)    | 40°C                 | 40°C                 |  |

Data are not binding. Hoyer reserves the right to implement changes without notice. The extent of data are not equivalent to nameplate on the motors.