



- | | | | | | | | | | | | | | | | |
|---|---|--|-----|---|-------------|----------------|----------|-----------------------------------|--|-------------------------------|----------------|--|--------------|-------|----------|
| Mounting tolerance | | <div>HOYER</div> <div>EXCEEDING EXPECTATIONS</div> | | Hoyer Motors | | | | DEBUR AND
BREAK SHARP
EDGES | | DRAWING NOT IN SCALE | | | | | |
| Dimensions range | Tolerance | | | Over Hadstenvej 42, DK-8370 Hadsten
Tel : +45 86982111
Fax: +45 86981779
www.hoyermotors.com | | | | OUTLINE DRAWING | | TITLE:

HMC3-315S-4p-B5 | | | | | |
| 0<D≤400 | ±10 | | | REV. | LOCATION | DESCRIPTION | DATE | | | | | | | RESP. | APPROVED |
| 400<D≤1000 | ±20 | | | | | | | DWG NO.:

TD-ID-D90105 | | | | | | A3 | |
| 1000<D≤2000 | ±30 | 0 | N/A | First issued | 09/10/2024 | L&T | Hoyer | | | | | | | | |
| 2000<D≤4000 | ±35 | | | | | | | | | | | | | | |
| 4000<D≤8000 | ±40 | | | | | | | | | | | | | | |
| Unit: mm | | | | | | | | | | | | | | | |
|  | Representation of the machine is illustrative only | | | Protection: | IEC 60034-5 | Machined Part: | ISO 2768 | SCALE: 1:10 | | | Weight: 876 kg | | SHEET 1 OF 1 | | |
| | Some features may not be represented | | | Dimension: | IEC 60072 | Weld Constr: | ISO 8015 | | | | | | | | |
| | For installation or maintenance, consult operation manual | | | Tolerance: | ISO 286 | Castings: | ISO 8062 | | | | | | | | |
| | | | | Key: | IEC 60072 | | | | | | | | | | |