



- | | | | | | | | | | | | | | | |
|---|---|--|--|---|-------------|----------------|-----------------------------------|-----------------------------|----------------------|--|--------------------------------|--------------|--|--|
| Mounting tolerance | | <div>HOYER</div> <div>EXCEEDING EXPECTATIONS</div> | | Hoyer Motors
Over Hadstenvej 42, DK-8370 Hadsten
Tel : +45 86982111
Fax: +45 86981779
www.hoyermotors.com | | | DEBUR AND
BREAK SHARP
EDGES | | DRAWING NOT IN SCALE | | | | | |
| Dimensions range | | | | | | | | | Tolerance | | OUTLINE DRAWING | | | |
| 0<D≤400 | | | | | | | | | ±10 | | TITLE:

HMC4-315S-6p-B35 | | | |
| 400<D≤1000 | | ±20 | | | | | | | | | | | | |
| 1000<D≤2000 | | ±30 | | | | | | | | | | | | |
| 2000<D≤4000 | | ±35 | | | | | | | | | | | | |
| 4000<D≤8000 | | ±40 | | | | | | | | | | | | |
| Unit: mm | | | | | | | | | | | | | | |
|  | Representation of the machine is illustrative only | | | Protection: | IEC 60034-5 | Machined Part: | ISO 2768 | DWG NO.:

TD-ID-D2079 | | | A3 | | | |
| | Some features may not be represented | | | Dimension: | IEC 60072 | Weld Constr: | ISO 8015 | | | | | | | |
| | For installation or maintenance, consult operation manual | | | Tolerance: | ISO 286 | Castings: | ISO 8062 | SCALE:1:1 | | | Weight: 797 kg | SHEET 1 OF 1 | | |
| | | | | Key: | IEC 60072 | | | | | | | | | |