

# Vibration sensor

Type: KPV200

---

## Application

- For measuring vibration
- Predictive maintenance

## Properties

- RS485 Modbus communication
- Wide frequency range
- 0-1600Hz, 0-800Hz, 0-400Hz, 0-200Hz, 0-100Hz and 1-50 Hz
- 128 Bin FFT output
- Vibration g range selectable from  $\pm 2g$  to  $\pm 16g$
- Measures in three directions, X, Y and Z
- Ambient temperature min/max:  $-40/+85^{\circ}\text{C}$
- Build-in intelligent alarm system
- Plug and Play solution
- User friendly software



---

## Electrical specifications

### Supply

10-28 VDC

### Output


RS485 Modbus protocol

### Connection: M12

Pin1	+10-28V
Pin2	RS485A
Pin3	0V
Pin4	RS485B

## Functionality

- The sensor is built for measuring vibrations
- The main components of the sensor are an accelerometer for vibration measurement and a DSP processor for data processing
- Data output is a 128 Bin FFT array.



## Environmental

### Temperatures

Temperature on electronics:  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$

### EMS

Emission: Domestic, EN 61000-6-3

Immunity: Industrial, EN 61000-6-2